

PELI LEGENDARY GUARANTEE OF EXCELLENCE

Peli Products, S.L.U. guarantees its products against breakage or defects in workmanship. Peli™ injection moulded cases are guaranteed to be watertight to a depth of 1 meter (3.3 feet) for 30 minutes (IP 67) if properly closed with undamaged o-ring in place unless otherwise stated. Peli's liability is limited to the case and not its contents or foam. All warranty claims of any nature are barred if the container has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to http://www.peli.com/en/content/guarantee-excellence for full details.

U.S.A.

U.S.A. & GLOBAL **HEADQUARTERS**

23215 Early Avenue Torrance, CA 90505 USA Tel 310.326.4700 800.473.5422 (Outside CA) Fax 310.326.3311

DEERFIELD

PELI HARDIGG CASES **USA HEADQUARTERS** 147 North Main Street South Deerfield, MA 01373 Tel (800) 542-7344 Fax (413) 665-8330 www.peli.com

EUROPE

FOR INFORMATION ON PELI LIGHTS, PELI CASES AND PELI STORM CASES IN EUROPE:

EUROPE, MIDDLE EAST & AFRICA HQ

PELI PRODUCTS, S.L.U. C/ Provença, 388 Planta 7 08025 • Barcelona, Spain Tel +34 934 674 999 Fax +34 934 877 393 www.peli.com

FRANCE

PELI PRODUCTS FRANCE S.A.S. 487 rue Léopold Le Hon 01000 • Bourg en Bresse, France Tel +33 4 74 22 80 40 Fax +33 4 74 22 09 34 www.peli.com

GERMANY

PELI PRODUCTS GERMANY GmbH Graf-Adolf-Platz 15 40213 • Düsseldorf, Germany Tel +49 (0) 211 882 42 401 Fax +49 (0) 211 882 42 200 www.peli.com

ADVANCED AREA LIGHTING GROUP PELI AALG LTD.

4 Chater Court Halifax Drive • Market Deeping Peterborough PE6 8AH, United Kingdom Tel +44 (0) 1778 349000 Fax +44 (0) 1778 349004 aalg.peli.com

UAE

PELICAN PRODUCTS MIDDLE EAST FZE P.O. Box 10559 • Ras Al Khaimah **United Arab Emirates** Tel +971 (0) 7 2076282 Fax +971 (0) 7 2076283

* We also have offices in Canada, Japan, China, Australia, South Korea and India

FOR INFORMATION ON PELI STORM OR PELI HARDIGG CASES IN EUROPE:

PELI-HARDIGG UK CASE CENTER Unit 4, Brookfield Industrial Estate

Leacon Road Ashford Kent TN23 4TU Tel +44 (0) 1233 895895

PELI-HARDIGG FRANCE **CASE CENTER**

20/22 Rue des Petits Hôtels 75010 Paris, France Tel +33 (0)1 44 83 95 63

PELI



DISTRIBUTED BY:



©2011 Peli Products S.L.U. All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., a U.S. corporation, its subsidiaries and/or affiliates. EU CODE: 0030-STM-001E JUL '11 All details included in this brochure are correct when printed but for most updated information please visit www.peli.com





You've got equipment to protect, and a Peli Storm Case is the best way to do it. Why? It's all about the resin: our proprietary HPX® polymer is proven to resist mpacts even in low temperature laboratory

But the real proof is in the

bragging rights that come with survival. Because to a Peli Storm Case, whether falling from a helicopter, crashing down class V rapids or taking a hit in the center lane of the New Jersey turnpike is all in a day's work.



Press & Pull® Latches

These smooth-opening, dependable, patented latches hold tight under pressure and impact despite fast-opening performance. Tested to over 180 Kg, yet open with a simple release button.

Moulded-In Lockable Hasps

Twin mating hasp holes on the rim of the case allow attachment of padlocks to keep your gear in and thieves out. And check out Peli's TSA approved cable padlock. Now you can check your baggage with confidence while flying in the USA. The Travel Security Agency has the key, and you have the combination.

















Rugged In-Line Wheels

Shielded from dust, dirt and other contaminants - ball bearing wheels provide low-friction, low-drag rolling with retractable handles for easy movement of heavy loads. Look for the icon for availability on select models.

Double-Layer, Soft-Grip Handles

When the weather goes south you'll find a secure grip that won't slip. An in-tool vulcanizing process over-moulds the grips to the polymer handle for a lifetime of dependable performance.



Vortex® Pressure Release Valve

The built-in technology of Peli Storm Cases automatic pressure equalization valve is also a patented feature. Air travel prevents vacuum lock to make opening the case natural even

after extreme altitude changes. At the same time, the microscopic filter blocks water molecules and dust particles so your gear stays clean in the Gobi and dry on the Nile.

0

0

0

0

0

0

0

- All cases available with no foam as an option - iM2050 through iM2500 meet airline

iM3100 through iM3300 come with

0

S (standard), O (optional) **Available as add-on kits only. Require additional assembly

carry-on regulations

multilayer foam

0

0

0

S

S

> Specifications, Features and Options

CAT #	Interior Dimensions*	Exterior Dimensions	Weight	Clrs
iM2050	9.5" L x 7.5" W x 4.25" H (24.1 x 19 x 10.8 cm)	11.8" L x 9.8" W x 4.7" H (30 x 24.9 x 11.9 cm)	2.7 lbs. (1.2 kg)	
iM2075	9.5" L x 7.5" W x 7.25" H (24.1 x 19 x 18.4 cm)	11.8" L x 9.8" W x 7.7" H (30 x 24.9 x 19.6 cm)	3.3 lbs. (1.5 kg)	
i M 2100	13" L x 9.2" W x 6" H (33 x 23.4 x 15.2 cm)	14.2" L x 11.4" W x 6.5" H (36.1 x 28.9 x 16.5 cm)	4.2 lbs. (1.9 kg)	
i M 2200	15" L x 10.5" W x 6" H (38.1 x 26.7 x 15.2 cm)	16.2" L x 12.7" W x 6.6" H (41.1 x 32.2 x 16.8 cm)	4.9 lbs. (2.2 kg)	
iM2300	17" L x 11.7" W x 6.2" H (43.2 x 29.7 x 15.7 cm)	18.2" L x 13.4" W x 6.7" H (46.2 x 34 x 17 cm)	5.8 lbs. (2.6 kg)	
iM2306	17" L x 6.3" W x 6.2" H (43.2 x 16 x 15.7 cm)	18.2" L x 8.4" W x 6.7" H (46.2 x 21.3 x 17 cm)	4.3 lbs. (2.0 kg)	
iM2370	18.2" L x 12.1" W x 5.2" H (46.2 x 30.7 x 13.2 cm)	20" L x 14.7" W x 5.8" H (50.8 x 37.3 x 14.7 cm)	5.7 lbs. (2.6 kg)	
iM2400	18" L x 13" W x 6.7" H (45.7 x 33 x 17 cm)	19.2" L x 15.2" W x 7.3" H (48.7 x 38.6 x 18.5 cm)	6.5 lbs. (3.0 kg)	
iM2450	18" L x 13" W x 8.4" H (45.7 x 33 x 21.3 cm)	19.2" L x 15.3" W x 9" H (48.7 x 38.6 x 22.9 cm)	7.4 lbs. (3.4 kg)	
iM2500	20.5" L x 11.5" W x 7.2" H (52 x 29.2 x 18.3 cm)	21.7" L x 14.1" W x 8.9" H (55.1 x 35.8 x 22.6 cm)	11 lbs. (5.0 kg)	
iM2600	20" L x 14" W x 7.7" H (50.8 x 35.5 x 19.6 cm)	21.2" L x 16" W x 8.3" H (53.8 x 40.6 x 21.1 cm)	8.5 lbs. (3.9 kg)	
iM2620	20" L x 14" W x 10" H (50.8 x 35.5 x 25.4 cm)	21.2" L x 16" W x 10.6" H (53.8 x 40.6 x 26.9 cm)	12.5 lbs. (5.7 kg)	
iM2700	22" L x 17" W x 8" H (55.9 x 43.2 x 20.3 cm)	24.6" L x 19.7" W x 8.6" H (62.5 x 50 x 21.8 cm)	11.1 lbs. (5.0 kg)	
iM2720	22" L x 17" W x 10" H (55.9 x 43.2 x 25.4 cm)	24.6" L x 19.7" W x 11.7" H (62.5 x 50 x 29.7 cm)	16.8 lbs. (7.6 kg)	
iM2750	22" L x 17" W x 12.7" H (55.9 x 43.2 x 32.2 cm)	24.6" L x 19.7" W x 14.4" H (62.5 x 50 x 36.6 cm)	18.5 lbs. (8.4 kg)	
iM2875	22.5" L x 21.1" W x 11.4" H (57.1 x 53.6 x 28.9 cm)	24.9" L x 23.7" W x 13.1" H (63.2 x 60.2 x 33.3 cm)	20.1 lbs. (9.1 kg)	
iM2950	29" L x 18" W x 10.5" H (73.6 x 45.7 x 26.7 cm)	31.3" L x 20.4" W x 12.2" H (79.5 x 51.8 x 31 cm)	20.8 lbs. (9.5 kg)	
iM2975	29" L x 18" W x 13.8" H (73.6 x 45.7 x 35 cm)	31.3" L x 20.4" W x 15.5" H (79.5 x 51.8 x 39.4 cm)	22.5 lbs. (10.2 kg)	
iM3075	29.8" L x 20.8" W x 17.8" H (75.7 x 52.8 x 45.2 cm)	33.3" L x 24.4" W x 19.3" H (84.5 x 62 x 49 cm)	31.5 lbs. (14.3 kg)	
iM3100	36.5" L x 14" W x 6" H (92.7 x 35.5 x 15.2 cm)	39.8" L x 16.5" W x 6.7" H (101.1 x 41.9 x 17 cm)	15.2 lbs. (6.9 kg)	
iM3200	44" L x 14" W x 6" H (111.7 x 35.5 x 15.2 cm)	47.2" L x 16.5" W x 6.7" H (119.8 x 41.9 x 17 cm)	17.7 lbs. (8.0 kg)	
iM3220	44" L x 14" W x 8.5" H (111.7 x 35.5 x 21.6 cm)	47.2" L x 16.5" W x 9.2" H (119.8 x 41.9 x 23.4 cm)	20.4 lbs. (9.3 kg)	
iM3300	50.5" L x 14" W x 6" H (128.2 x 35.5 x 15.2 cm)	53.8" L x 16.5" W x 6.7" H (136.6 x 41.9 x 17 cm)	19 lbs. (8.6 kg)	

*Lid height included in interior dimensions: iM2050-iM2075 1.5 inch (3.8 cm) lid, iM2370 1.7 inch (4.3 cm) lid, iM3075 4 inch (10.2 cm) lid, iM2100-3300 2 inch (5.1 cm) lid