

材料安全数据表

Material Safety Data Sheet

1. Identification of the product and supplier (产品和厂商信息)	
产品名称 Name of goods	锂离子电池 Li-ion Battery
产品型号 Type/Mode	18650 (LG) 3.7V 2600mAh 9.62Wh
制造商 Manufacturer	深圳市泰量电子有限公司 Shenzhen Tenerg Electronic Co., Ltd.
制造商地址 Manufacturer address	广东省深圳市龙华新区民治大道 58 号恒润大厦 638 室 Room 638, Henrun Building, No. 58, Minzhi Road. Longhua District, Shenzhen, Guangdong, China.
生产厂 Factory	东莞市海量能源科技有限公司 Dongguan Hilion Battery Co., Ltd.
生产厂地址 Factory address	广东省东莞市塘厦镇科苑诚信息产业园鹿乙路 A16 号 C13 C13 Building, No. A16, Luyi Road. Keyuaricheng IT Industry Park, TangxiaTown, Dongguan, Guangdong, China.
鉴定依据 Inspection according to	EEC Directive 93/112/EC 联合国《关于危险品货物运输的建议书》 UN "Recommendations on the TRANSPORT OF DANGEROUS GOODS"
紧急联系电话 Eergency telephone call	+86-755 33231651
签发日期/Issue date :2018-01-02	

Approved by:
Tested by:

Reviewed by:

批准: 袁平秋

审核: 季东

编制: 唐波

Shenzhen Tenerg Electronic Co., Ltd.

Room 638, Henrun Building, No. 58, Minzhi Road, Longhua District, Shenzhen, Guangdong, China.

Tel: +86-755-3323 1651 Fax: +86-755-3323 1686

2. Composition/Information on Ingredient (成分/组成信息)

危险成分 (化学名称) Hazardous Ingredients (Chemical Name)	含量及含量百分比 (%) Concentration or concentration ranges (%)	CAS 编号 CAS Number
钴酸锂/Lithium Cobalt Oxide	37.82%	12190-79-3
聚偏氟乙烯/Polyvinylidene (PVDF)	1.46%	24937-79-9
铝/Aluminium (Al)	9.03%	7429-90-5
石墨/Graphite	16.48%	7782-42-5
丁苯橡胶/Styrene-Butadiene Rubber (SBR)	0.39%	61789-96-6
羧甲基纤维/Carboxymethylcellulose	0.31%	9000-11-7
铜/Copper (Cu)	9.74%	7440-50-8
镍/Nickel (Ni)	1.08%	7440-02-0
六氟磷酸锂/Lithium Hexafluorophosphate	18.56%	21324-40-3
聚乙烯/Polyethylene	3.03%	9002-88-4
尼龙/Nylon	0.8%	24937-16-4
聚丙烯/Polypropylene	1.3%	9003-07-0

3. Hazards Identification (主要危险性鉴定)

爆炸危险性 Explosive risk	该物品不属于爆炸物品 This article does not belong to the explosion dangerous goods
易燃危险性 Flammable risk	该物品不属于易燃危险品 This article does not belong to the flammable material
氧化危险性 Oxidtion risk	该物品不属于氧化危险品 This article does not belong to the oxidation of dangerous goods
毒害危险性 Toxic risk	该物品不属于毒害危险品 This article does not belong to the toxic dangerous goods
放射危险性 Radioactive risk	该物品不属于放射危险品 This article does not belong to the radiation of dangerous goods
腐蚀危险性 Mordant risk	该物品不属于腐蚀危险品 This article does not belong to the corrosion of dangerous goods
其他危险性 Other risk	该物品为锂离子电池, 瓦时率为 9.62Wh This article is Li-ion Battery, Watt hour rate 9.62Wh

4. First aid measures (急救措施)

Shenzhen Tenergy Electronic Co., Ltd.

Room 638, Henrun Building, No.58, Minzhi Road, Longhua District, Shenzhen, Guangdong, China.

Tel: +86-755-3323 1651 Fax: +86-755-3323 1686

Eye

Flush eye with plenty of water for at least 15 minutes ,occasionally lifting the upper and lower eyelids.Get medical aid.

Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes .Get medical aid.

Inhalation

Remove from exposure and move to fresh air immediately.Use oxygen if available

Ingestion

Give at least 2 glasses of milk or water .Induce vomiting unless patient is unconscious ,Call a physician.

5. Fire-fighting measures (消防措施)

Flash Point:N/A.

Auto-Ignition Temperature:N/A .

Extinguishing Media:Water, CO2.

Special Fire-Fighting Procedures

Self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Cell may vent when subjected to excessive heat -exposing battery contents.

Hazardous Combustion Products

Carbon monoxide, carbon dioxide, lithium oxide fumes.

6. Accidental release measures (泄露应急处理)

Steps to be Taken in case Material is Released or spilled

If the battery material is released , remove personnel from area until fumes dissipate .Provide maximum ventilation to clear out hazardous gases .Wipe it up with a cloth, ,and dispose of it in a plastic bag and put into a steel can .The preferred response is to leave the area and allow the battery to cool and vapors to dissipate.Provide maximum ventilation.Avoid skin and eye contact or inhalation of vapors.Remove spilled liquid with absorbent and incinerate.

Waste Disposal Method

It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil.

7. Handling and storage (操作处置和储存)

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container.

Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire.

Do not crush or puncture the battery, or immerse in liquids.

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse .Storage preferably in cool, dry and ventilated area, which is subject to

Shenzhen Tenerg Electronic Co.,Ltd.

Room 638, Henrun Building, No.58, Minzhi Road, Longhua District, Shenzhen, Guangdong, China.

Tel:+86-755-3323 1651 Fax:+86-755-3323 1686

little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

Other Precautions

The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do

not short or install with incorrect polarity.

8. Exposure controls/personal protection (接触控制/个人防护)

Respiratory protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores.

Respiratory protection is not necessary under conditions of normal use.

Ventilation

Not necessary under conditions of normal use.

Other protective Clothing or Equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting battery

Respiratory protection, protective Gloves, Protective Clothing and safety glass with side shields.

9. Physical and chemical properties (物理和化学特征)

Appearance: Prismatic shape

Odour: If leaking, smells of medical ether.

pH: Not applicable as supplied.

Flash Point: Not applicable unless individual components exposed.

Flammability: Not applicable unless individual components exposed,

Relative density: Not applicable unless individual components exposed,

Solubility (water): Not applicable unless individual components exposed,

Solubility (other): Not applicable unless individual components exposed,

10. Stability and reactivity (稳定性和反应活性)

Stability: Product is stable under conditions described in Section 7.

Conditions to avoid: Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.

Materials to avoid: Oxidising agents, alkalis, water.

Hazardous Decomposition Products: Toxic Fumes, and may form peroxides.

Hazardous Polymerization: N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons.

11. Toxicological information (毒理性资料)

Shenzhen Teneng Electronic Co., Ltd.

Room 638, Henrun Building, No. 58, Minzhi Road, Longhua District, Shenzhen, Guangdong, China.

Tel: +86-755-3323 1651 Fax: +86-755-3323 1686

Signs & symptoms:None, unless battery tuptures.

In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.

Inhalation:Lung irritant.

Skin contact:Skin irritant

Eye contact:Eye irritant

Ingestion:Poisoning if swallowed

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to server irritation, burning and dryness of the skin may occur, Target organs nerves, licer and kidneys.

12. Ecological informtion(生态学资料)

Mammalian effects:None known at present.

Eco-toxicity:None known at present.

Bioaccumulation potential: Slowly Bio-degradable.

Enviromental fate:None known environmental hazards at present.

13. Disposal consideration(废弃处置)

Do not incinerate, or subject cells to temperaure in excess of 70°C, Such abuse can result in loss of seal leakage, And/or cell explosion. Dispose of in accordance with appropriate local regulations.

14. Transport information(运输信息)

Label for conveyance:Lithium Battery label.

UN Number:UN3481

Packing Group:N/A

EmS No:4.1-0.6

Marine pollutant: No

Proper Shipping name: Lithium ion batteries contained in equipment. (including Lithium ion polymer batteries)

Hazar Classification:The goods shall be complied with the requipemets of Section II of PackingInstructions 967 of 59thDGR Manual of IATA(2018edition), including the passing fo the UN38.3test.

And also complies with the Special Provision 188 and 230 of IMDG CODE (Amdt.37-14)2014Edition. The products are not subject to dangerous goods.

15. Regulation information(法规信息)

Law information

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safery and Health Act》 (OSHA)

Shenzhen Tenerg Electronic Co.,Ltd.

Room 638, Henrun Building, No.58, Minzhi Road, Longhua District, Shenzhen, Guangdong, China.

Tel:+86-755-3323 1651 Fax:+86-755-3323 1686

6 / 6

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act》 (CPSA)

《Federal Environmental Pollution Control Act》 (FEPCA)

《The Oil Pollution Act》 (OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313) 》 (SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》 (CWA)

《California Proposition 65 》

《Code of Federal Regulations》 (CFR)

In accordance with all Federal, State and local laws.

16. Other information (其他信息)

This information is not effective to all the batteries manufactured by Dongguan Hilion Battery Co., Ltd. This information comes from reliable sources, but no warranty is made to the completeness and accuracy of information contained in Dongguan UTL Electronic Technology Co., Ltd. doesn't assume responsibility for any damage or loss because of misuse of batteries. User's should grasp the correct use method and be responsible for the use of batteries.

Shenzhen Tenerg Electronic Co., Ltd.

Room 638, Henrun Building, No. 58, Minzhi Road, Longhua District, Shenzhen, Guangdong, China.

Tel: +86-755-3323 1651 Fax: +86-755-3323 1686